



**BOSCH**

Invented for life



# Advantage Line Quick Selection Guide

## Professional CCTV Solutions

Advantage Line

## Table of Content

<b>IP Cameras</b>	<b>2</b>
Box IP Cameras	2
Dome IP Cameras	3
Micro Dome IP Cameras	4
Bullet IP Cameras	5
<b>Analog Cameras</b>	<b>6</b>
Box Cameras	6
MiniDomes Indoor	7
MiniDomes Outdoor	8
AutoDome Mini Outdoor	9
IR Bullet Cameras Outdoor	10
Bullet Cameras	11
<b>Accessories</b>	<b>12</b>
<b>Digital Video Recorders</b>	<b>13</b>

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## IP Cameras I



### ► Box Cameras

NBC-225-P

NBC-255-P

NBC-265-P

NBC-255-W



NBC-265-W



<b>Imaging</b>	<b>Image Sensor Type</b>	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS
	<b>Day/Night</b>	—	—	—	—	—
	<b>WDR</b>	—	—	—	—	—
	<b>IR Sensitive</b>	—	—	—	—	—
	<b>Motion Detection</b>	Yes	Yes	Yes	Yes	Yes
	<b>Privacy Zones</b>	—	—	—	—	—
	<b>IR Illumination LEDs</b>	—	—	—	—	—
<b>Max. Resolution</b>	<b>Color</b>	VGA (640 x 480)	VGA (640 x 480)	HD 720p (1280 x 720)	VGA (640 x 480)	HD 720p (1280 x 720)
	<b>B/W</b>	—	—	—	—	—
<b>Min. Illumination</b>	<b>Color</b>	1.0 lux	1.0 lux	1.0 lux	1.0 lux	1.0 lux
	<b>B/W</b>	—	—	—	—	—
<b>Lens</b>		4.9 mm Fixed	2.8-10 mm Manual-iris	2.8 - 8 mm $\square$ Manual-iris	2.8 - 10 mm $\square$ Manual-iris	2.8 - 8 mm $\square$ Manual-iris
<b>Night Vision / Infrared Range</b>		—	—	—	—	—
<b>Output Connection</b>		Ethernet, RJ45	Ethernet, RJ45	Ethernet, RJ45	WiFi / Ethernet, RJ45	WiFi / Ethernet, RJ45
<b>Wifi</b>		—	—	—	IEEE 802.11b/g	IEEE 802.11b/g
<b>Storage</b>		SDHC Card	SDHC Card	SDHC Card	SDHC Card	SDHC Card
<b>Environment</b>	<b>Operating Temperature</b>	0° to 50° C	0° to 50° C	0° to 50° C	0° to 45° C	0° to 45° C
	<b>All-weather Rating</b>	—	—	—	—	—
<b>Power</b>	<b>Max. Consumption</b>	3.36 W	3.36 W	3.36 W	4.6 W	4.6 W
	<b>Supply</b>	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## IP Cameras I



### ► Dome Cameras - IP 200 Series

NDC-225-P

NDC-255-P

NDC-225-PI



NDC-265-P

NDN-265-PIO



<b>Imaging</b>	<b>Image Sensor Type</b>	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS
	<b>Day/Night</b>	—	—	Yes	—	Yes
	<b>WDR</b>	—	—	—	—	—
	<b>IR Sensitive</b>	—	—	Yes	—	—
	<b>Motion Detection</b>	Yes	Yes	Yes	Yes	Yes
	<b>Privacy Zones</b>	—	—	—	—	—
	<b>IR Illumination LEDs</b>	—	—	33 @ 940 nm	—	15 @ 850 nm
<b>Max. Resolution</b>	<b>Color</b>	VGA (640 x 480)	VGA (640 x 480)	VGA (640 x 480)	HD 720p (1280 x 720)	HD 720p (1280 x 720)
	<b>B/W</b>	—	—	—	—	—
<b>Min. Illumination</b>	<b>Color</b>	1.0 lux	1.0 lux	1.0 lux	1.0 lux	1.0 lux
	<b>B/W</b>	—	—	0 lux (IR on)	—	—
<b>Lens</b>		4 mm Fixed	2.8-10 mm Auto-iris	4 mm Fixed	2.7 - 9 mm DC Auto-iris	2.7 - 9 mm DC Auto-iris
<b>Night Vision / Infrared Range</b>		—	—	15m	—	—
<b>Output Connection</b>		Ethernet, RJ45	Ethernet, RJ45	Ethernet, RJ45	Ethernet, RJ45	Ethernet, RJ45
<b>Wifi</b>		—	—	—	—	—
<b>Storage</b>		microSDHC Card	microSDHC Card	microSDHC Card	microSDHC Card	microSDHC Card
<b>Environment</b>	<b>Operating Temperature</b>	0° to 50° C	0° to 50° C	-10° to 50° C	-10° to 50° C	-20° to 50° C
	<b>All-weather Rating</b>	—	—	—	—	IP66, IK10
<b>Power</b>	<b>Max. Consumption</b>	4.1 W	4.1 W	6.6 W	4.1 W	4.1 W
	<b>Supply</b>	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## IP Cameras III



### ► Micro Dome Cameras

NDC-274-P

NDC-274-PT

NDC-284-PT

<b>Imaging</b>	<b>Image Sensor Type</b>	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS
	<b>Day/Night</b>	—	—	—
	<b>WDR</b>	—	—	—
	<b>IR Sensitive</b>	—	—	—
	<b>Motion Detection</b>	Yes	Yes	Yes
	<b>Privacy Zones</b>	—	—	—
	<b>IR Illumination LEDs</b>	—	—	—
<b>Max. Resolution</b>	<b>Color</b>	HD 1080p (1920 x 1080)	HD 1080p (1920 x 1080)	5 MegaPixel (2592x 1944)
	<b>B/W</b>	—	—	—
<b>Min. Illumination</b>	<b>Color</b>	0.3 lux	0.3 lux	0.3 lux
	<b>B/W</b>	—	—	—
<b>Lens</b>		4.37 mm Fixed	4.37 mm Fixed	3.74 mm Fixed
<b>Night Vision / Infrared Range</b>		—	—	—
<b>Output Connection</b>		Ethernet, RJ45	Ethernet, RJ45	Ethernet, RJ45
<b>Wifi</b>		—	—	—
<b>Storage</b>		microSDHC Card	microSDHC Card	microSDHC Card
<b>Environment</b>	<b>Operating Temperature</b>	-20° to 50° C	-20° to 50° C	-20° to 50° C
	<b>All-weather Rating</b>	—	IP66, IK08	IP66, IK08
<b>Power</b>	<b>Max. Consumption</b>	3.9 W	3.9 W	3.9 W
	<b>Supply</b>	+12 VDC or PoE	+12 VDC or PoE	+12 VDC or PoE

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## IP Cameras IV



### ► Bullet Cameras

NTC-255-PI



NTC-265-PI



<b>Imaging</b>	<b>Image Sensor Type</b>	1/4" CMOS	1/4" CMOS
	<b>Day/Night</b>	Yes	Yes
	<b>WDR</b>	—	—
	<b>IR Sensitive</b>	Yes	Yes
	<b>Motion Detection</b>	Yes	Yes
	<b>Privacy Zones</b>	—	—
	<b>IR Illumination LEDs</b>	32 @ 850 nm	32 @ 850 nm
<b>Max. Resolution</b>	<b>Color</b>	VGA (640 x 480)	HD 720p (1280 x 720)
	<b>B/W</b>	—	—
<b>Min. Illumination</b>	<b>Color</b>	1 lux (IR off)	1 lux (IR off)
	<b>B/W</b>	0 lux (IR on)	0 lux (IR on)
<b>Lens</b>		3.7 - 10 mm DC Auto-iris	2.7 - 9 mm DC Auto-iris
<b>Night Vision / Infrared Range</b>		25m	25m
<b>Output Connection</b>		Ethernet, RJ45	Ethernet, RJ45
<b>Wifi</b>		—	—
<b>Storage</b>		—	—
<b>Environment</b>	<b>Operating Temperature</b>	-20° to 55° C	-20° to 55° C
	<b>All-weather Rating</b>	IP66	IP66
<b>Power</b>	<b>Max. Consumption</b>	6 W	6 W
	<b>Supply</b>	+12 VDC or PoE	+12 VDC or PoE

# Advantage Line Quick Selection Guide - Professional CCTV Solutions Analog Cameras I



## ► Box Cameras

VBC-255-11

VBC-255-51

VBC-265-11

VBC-265-51

<b>Imaging</b>	<b>Image Sensor Type</b>	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
	<b>Day/Night</b>	NightSense	NightSense	Yes	Yes
	<b>WDR</b>	—	—	—	—
	<b>IR Sensitive</b>	—	—	Yes	Yes
	<b>Motion Detection</b>	—	—	—	—
	<b>Privacy Zones</b>	—	—	—	—
	<b>IR Illumination LEDs</b>	—	—	—	—
<b>Max. Resolution</b>	<b>Color</b>	540 TVL	540 TVL	540 TVL	540 TVL
	<b>B/W</b>	—	—	540 TVL	540 TVL
<b>Min. Illumination</b>	<b>Color</b>	0.3 lux	0.3 lux	0.3 lux	0.3 lux
	<b>B/W</b>	0.12 lux	0.12 lux	0.012 lux	0.012 lux
<b>Lens</b>	<b>Lens</b>	—	—	—	—
	<b>Optical Zoom</b>	—	—	—	—
<b>Night Vision / Infrared Range</b>		—	—	—	—
<b>Output Connection</b>	<b>Video Output</b>	BNC Connector	BNC Connector	BNC Connector	BNC Connector
	<b>PTC Control</b>	—	—	—	—
<b>Storage</b>		—	—	—	—
<b>Environment</b>	<b>Operating Temperature</b>	-20° to 50° C	-20° to 50° C	-20° to 50° C	-20° to 50° C
	<b>All-weather Rating</b>	—	—	—	—
<b>Power</b>	<b>Max. Consumption</b>	4.0 W	4.0 W	4.0 W	4.0 W
	<b>Supply</b>	24 VAC, 12 VDC	230VAC	24 VAC, 12 VDC	230VAC

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Analog Cameras II



### ► MiniDomes Indoor

VDC-250F04-20

VDC-260-V04-20

VDC-275-10

VDN-276-10

VDN-295-10

<b>Imaging</b>	<b>Image Sensor Type</b>	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
	<b>Day/Night</b>	Yes	Yes	—	Yes	Yes
	<b>WDR</b>	—	—	—	—	Yes
	<b>IR Sensitive</b>	Yes	Yes	—	Yes	Yes
	<b>Motion Detection</b>	4 Zones	4 Zones	4 Zones	4 Zones	4 Zones
	<b>Privacy Zones</b>	4 Zones	4 Zones	4 Zones	4 Zones	15 Zones
	<b>IR Illumination LEDs</b>	—	—	—	—	—
<b>Max. Resolution</b>	<b>Color</b>	540 TVL	540 TVL	720 TVL*	720 TVL*	720 TVL*
	<b>B/W</b>	580 TVL	580 TVL	n/a	n/a	n/a
<b>Min. Illumination</b>	<b>Color</b>	0.15 lux	0.15 lux	0.12 lux	0.12 lux	0.15 lux
	<b>B/W</b>	0.05 lux	0.05 lux	0.07 lux	0.07 lux	0.05 lux
<b>Lens</b>	<b>Lens</b>	3.8 mm Fixed	3.8 - 9.5 mm DC Iris	2.8 - 10.5 mm Auto-iris	2.8 - 10.5 mm Auto-iris	2.8 - 10.5 mm Auto-iris
	<b>Optical Zoom</b>	—	—	—	—	—
<b>Night Vision / Infrared Range</b>		—	—	n/a	n/a	n/a
<b>Output Connection</b>	<b>Video Output</b>	BNC Connector	BNC Connector	BNC Connector	BNC Connector	BNC Connector
	<b>PTC Control</b>	—	—	—	—	—
<b>Storage</b>		—	—	—	—	—
<b>Environment</b>	<b>Operating Temperature</b>	-10° to 50° C	-10° to 50° C	-10° to 50° C	-10° to 50° C	-10° to 50° C
	<b>All-weather Rating</b>	—	—	—	—	—
<b>Power</b>	<b>Max. Consumption</b>	3.8 W	3.8 W	3.6 W	3.6 W	3.6 W
	<b>Supply</b>	24 VAC, 12 VDC	24 VAC, 12 VDC	24 VAC, 12 VDC	24 VAC, 12 VDC	24 VAC, 12 VDC

\* = sensor resolution



# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Analog Cameras III



### ► MiniDomes Outdoor

VDC-240V03-2

VDN-240V03-2

VDI-240V03-2



VDI-245V03-2



Imaging	<b>Image Sensor Type</b>	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
	<b>Day/Night</b>	—	Yes	Yes	Yes
	<b>WDR</b>	—	—	—	—
	<b>IR Sensitive</b>	—	Yes	Yes	Yes
	<b>Motion Detection</b>	4 Zones	4 Zones	—	64 Zones
	<b>Privacy Zones</b>	4 Zones	4 Zones	—	4 Zones
	<b>IR Illumination LEDs</b>	—	—	20 @ 850 nm	18 @ 850 nm
Max. Resolution	<b>Color</b>	540 TVL	540 TVL	540 TVL	540 TVL
	<b>B/W</b>	n/a	580 TVL	580 TVL	540 TVL
Min. Illumination	<b>Color</b>	0.05 lux	0.05 lux	0.05 lux	—
	<b>B/W</b>	n/a	0.005 lux	0 lux (IR on)	0 lux (IR on)
Lens	<b>Lens</b>	2.8 - 10.5 mm Auto-iris	2.8 - 10.5 mm Auto-iris	3.8 - 9.5 mm Auto-iris	3 - 12 mm Auto-iris
	<b>Optical Zoom</b>	—	—	—	—
Night Vision / Infrared Range		n/a	n/a	20m	18m
Input/Output Connection	<b>Video Output</b>	BNC Connector	BNC Connector	BNC Connector	BNC Connector
	<b>PTC Control</b>	—	—	—	—
Storage		—	—	—	—
Environment	<b>Operating Temperature</b>	-10° to 50° C	-10° to 50° C	-10° to 50° C	-30° to 55° C
	<b>All-weather Rating</b>	IP66	IP66	IP66	IP66
Power	<b>Max. Consumption</b>	3.6 W	3.6 W	6 W	4.5 W
	<b>Supply</b>	24 VAC, 12 VDC	24 VAC, 12 VDC	24 VAC, 12 VDC	24 VAC, 12 VDC

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Analog Cameras IV



### ► AutoDome Mini Outdoor

VEZ-413-EWCS

VEZ-413-ECCS

VEZ-413-EWTS

VEZ-413-ECTS

<b>Imaging</b>	<b>Image Sensor Type</b>	1/4" CCD	1/4" CCD	1/4" CCD	1/4" CCD
	<b>Day/Night</b>	Yes	Yes	Yes	Yes
	<b>WDR</b>	Yes	Yes	Yes	Yes
	<b>IR Sensitive</b>	Yes	Yes	Yes	Yes
	<b>Motion Detection</b>	—	—	—	—
	<b>Privacy Zones</b>	15 Zones	15 Zones	15 Zones	15 Zones
	<b>IR Illumination LEDs</b>	—	—	—	—
<b>Max. Resolution</b>	<b>Color</b>	600 TVL	600 TVL	600 TVL	600 TVL
	<b>B/W</b>	600 TVL	600 TVL	600 TVL	600 TVL
<b>Min. Illumination</b>	<b>Color</b>	0.2 lux	0.2 lux	0.2 lux	0.2 lux
	<b>B/W</b>	0.001 lux	0.001 lux	0.001 lux	0.001 lux
<b>Lens</b>	<b>Lens</b>	3.5 - 104 mm	3.5 - 104 mm	3.5 - 104 mm	3.5 - 104 mm
	<b>Zoom</b>	Zoom	Zoom	Zoom	Zoom
	<b>Optical Zoom</b>	26X	26X	26X	26X
<b>Night Vision / Infrared Range</b>		—	—	—	—
<b>Input/Output Connection</b>	<b>Video Output</b>	BNC Connector	BNC Connector	BNC Connector	BNC Connector
	<b>PTC Control</b>	RS485	RS485	RS485	RS485
<b>Storage</b>		—	—	—	—
<b>Environment</b>	<b>Operating Temperature</b>	-40° to 50° C	-40° to 50° C	-40° to 50° C	-40° to 50° C
	<b>All-weather Rating</b>	IP66	IP66	IP66	IP66
<b>Power</b>	<b>Max. Consumption</b>	20W / 45W w.heater	20W / 45W w.heater	20W / 45W w.heater	20W / 45W w.heater
	<b>Supply</b>	24 VAC	24 VAC	24 VAC	24 VAC

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Analog Cameras V



### ► IR Bullet Cameras Outdoor

VTI-214F04-3



VTI-216V04-1



VTI-218V03-1



VTI-220V05-1



Imaging	<b>Image Sensor Type</b>	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
	<b>Day/Night</b>	Yes	Yes	Yes	Yes
	<b>WDR</b>	—	—	—	—
	<b>IR Sensitive</b>	Yes	Yes	Yes	Yes
	<b>Motion Detection</b>	—	—	64 Zones	64 Zones
	<b>Privacy Zones</b>	—	—	4 Zones	4 Zones
	<b>IR Illumination LEDs</b>	30 @ 850 nm	18 @ 850 nm	18 @ 850 nm	30 @ 850 nm
Max. Resolution	<b>Color</b>	380 TVL	520 TVL	540 TVL	540 TVL
	<b>B/W</b>	—	—	—	—
Min. Illumination	<b>Color</b>	—	—	—	—
	<b>B/W</b>	0 lux (IR on)	0 lux (IR on)	0 lux (IR on)	0 lux (IR on)
Lens	<b>Lens</b>	4 mm	3.8 - 9.5 mm	2.8 -12 mm	5 - 50 mm
		Fixed	DC Auto-iris	DC Auto-iris	DC Auto-iris
	<b>Optical Zoom</b>	—	—	—	—
Night Vision / Infrared Range		15 m	20 m	20 m	45 m
Input/Output Connection	<b>Video Output</b>	BNC Connector	BNC Connector	BNC Connector	BNC Connector
	<b>PTC Control</b>	—	—	—	—
Storage		—	—	—	—
Environment	<b>Operating Temperature</b>	-30° to 50° C	-30° to 55° C	-30° to 50° C	-30° to 55° C
	<b>All-weather Rating</b>	IP67	IP67	IP66	IP66
Power	<b>Max. Consumption</b>	4.2 W	4.2 W	6.7 W	8 W
	<b>Supply</b>	12 VDC	24 VAC and 12 VDC	24 VAC and 12 VDC	24 VAC and 12 VDC

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Analog Cameras VI



### ► Bullet Cameras

VTC-204F03-3

VTC-206F03-3

<b>Imaging</b>	<b>Image Sensor Type</b>	1/3" CCD	1/3" CCD
	<b>Day/Night</b>	—	—
	<b>WDR</b>	—	—
	<b>IR Sensitive</b>	—	—
	<b>Motion Detection</b>	—	—
	<b>Privacy Zones</b>	—	—
	<b>IR Illumination LEDs</b>	—	—
<b>Max. Resolution</b>	<b>Color</b>	380 TVL	600 TVL
	<b>B/W</b>	—	—
<b>Min. Illumination</b>	<b>Color</b>	0.5 lux	0.1 lux
	<b>B/W</b>	—	—
<b>Lens</b>	<b>Lens</b>	3.6 mm Fixed	3.6 mm Fixed
	<b>Optical Zoom</b>	—	—
<b>Night Vision / Infrared Range</b>		—	—
<b>Input/Output Connection</b>	<b>Video Output</b>	BNC Connector	BNC Connector
	<b>PTC Control</b>	—	—
<b>Storage</b>			
<b>Environment</b>	<b>Operating Temperature</b>	-10° to 50° C	-10° to 50° C
	<b>All-weather Rating</b>	IP67	IP67
<b>Power</b>	<b>Max. Consumption</b>	3.6 W	3.6 W
	<b>Supply</b>	12 VDC	12 VDC

# Advantage Line Quick Selection Guide - Professional CCTV Solutions Accessories



## Brackets AutoDome Mini



**VEZ-A4-PC**

VEZ-400 Pipe mount charcoal



**VEZ-A4-PW**

VEZ-400 Pipe mount white




**VEZ-A4-WC**

VEZ-400 Wall mount charcoal



**VEZ-A4-WW**

VEZ-400 Wall mount white



**VEZ-A4-IC**

VEZ-400 In-ceiling mount

## Brackets IP 200 Dome



**VDA-FMT IP200 Dome**

Flush mount ceiling kit IP 200 Dome  
NDC 225 / NDC 255 / NDC 265



**NDA-WMT IP200 Dome**

Wall mount IP 200 Dome



**NDA-MBR IP200 Dome**

Camera adaptor bracket IP 200 Dome

## Power Supplies



**UPA-2420-50**

Power supply unit 220 VAC 50Hz,  
24 VAC 20 VA out



**UPA-2450-50**

Power supply unit 220 VAC 50Hz,  
24 VAC 50 VA out



**UPA-1216-50**

Power supply unit 220 VAC 50Hz,  
12VDC 1A out, universal plug

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Digital Video Recorders I



### DVR 400 Series

### DVR 600 Series

		DVR 400 Series	DVR 600 Series
<b>System</b>	<b>Target System Size</b>	1 - 8 cameras	8 - 16 cameras
	<b>Operating System</b>	Embedded	Embedded
	<b>Rack Module</b>	No	Yes
	<b>SDK Available</b>	Yes (V4.4x)	Yes (V4.4x)
<b>Video</b>	<b>Input Channels</b>	4, 8	8, 16
	<b>Output</b>		
	<b>Looping Video</b>	Yes	Yes
	<b>Composite</b>	1	0
	<b>VGA</b>	Yes	2
	<b>HDMI</b>	No	Yes (DVR 670)
	<b>Spot Monitor</b>	1	1
<b>Audio</b>	<b>Input Channels</b>	1	4
	<b>Output Channels</b>	1	2
	<b>Synchronous Audio</b>	Yes	Yes
	<b>Associate Multiple Cameras to 1 Audio</b>	Yes	Yes
<b>Storage</b>	<b>Internal HDD/Expandable</b>	500 GB	500, 1000, 2000 GB
	<b>Export</b>		
	<b>Supported Devices</b>	USB 1.1 and USB 2.0	Internal CD/DVD Writer, USB 2.0
	<b>Data Format</b>	Native File Format	Native File Format
	<b>Back-up Mode</b>	n/a	Manual or Automatic

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Digital Video Recorders II



### DVR 400 Series

### DVR 600 Series

		DVR 400 Series	DVR 600 Series
Alarms	Inputs	4, 8	8, 16
	Relay Outputs	1 or 4	4
	Call up Pre-position on Dome Cameras	Yes	Yes
	Increase Frame Rate on Alarm	Yes	Yes
	Simultaneous Normal & Event Recording	Yes	Yes
	Multiple Camera Linking on Alarm Event	Yes	Yes
	Notification on Email	Yes	Yes
	Pre-alarm	Yes	Up to 30 seconds
	Motion Detection	Yes	Yes
Recording	Video Compression	H.264	H.264
	Frame Rate (IPS) / IPS per Camera	50IPS@4CIF (4ch)	100IPS@4CIF (8ch, 630/650)
		50IPS@4CIF (8ch)	100IPS@4CIF (16ch, 630/650)
			200IPS@4CIF (8ch, 670)
			400IPS@4CIF (16ch, 670)
	Rec. Resolution	CIF/2CIF/4CIF	CIF/2CIF/4CIF
	Individual Cameras Adjustment (IPS & Quality)	Yes	Yes
	Schedule Recording Modes	Day/Week/Specific Day/32 Exception Days	Day/Week/Specific Day/32 Exception Days

# Advantage Line Quick Selection Guide - Professional CCTV Solutions

## Digital Video Recorders III



### DVR 400 Series

### DVR 600 Series

	DVR 400 Series	DVR 600 Series		
Search	Timeline Search Bar (Color-coded)	Yes	Yes	
	Search Mode	Date time, Events, Motion, Smart Motion Search	Date time, Events, Motion, Smart Motion Search	
	Smart Motion Search	Yes	Yes	
Display	Live Resolution	704x576	704x576	
	Screen Division	Full, Sequence, 2x2, 3x3 (8ch)	Full, Sequence, 2x2, 3x2, 3x3, 4x4, 5+1, 7+1, 12+1	
Security	User Control	User Levels	3	3
		Camera Lockouts by User	Yes	Yes
		Set Viewing Permissions	Yes	Yes
Remote Access	Data Integrity Check (Watermarking, etc.)	Yes	Yes	
	Network	10/100 Ethernet	10/100 Ethernet	
	Web Browser Access	Yes	Yes	
	Simultaneous Accessible Users	4	4	
	Admin control	Yes	Yes	
Other	PTZ Control	Yes	Yes	
	Export Options	Native File Format and .AVI	Native File Format and .AVI	
	Instant Playback	Yes	Yes	
	Digital Zoom (Live)	Yes	Yes	
	PTZ Joystick Control	No	Yes	